

MATERIAL SAFETY DATA SHEET

Page: 1

PRODUCT NAME: Red Oxide Shop Primer

PRODUCT CODE: 30-37

HMIS CODES: H F R P
2 3 0 3

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Pruett-Schaffer Chemical Co.
 ADDRESS: 3327 Stafford Street Pittsburgh PA 15204
 EMERGENCY PHONE: 1-800-633-8253 INFORMATION PHONE: 1-412-771-2000
 REVISION DATE: 01/31/01 NAME OF PREPARER: Robert P. Barry

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP Deg F	WEIGHT PERCENT
Aliphatic Petroleum Hydrocarbons (VM&P Naptha) ACGIH TLV: 300ppm TWA, OSHA PEL: 300ppm TWA	8032-32-4	5 60	24.14
Film Forming Resin	Not Avail.		14.00
Red Iron Oxide, inert pigment ACGIH TLV: 5 mg/m3, OSHA PEL: 10 mg/m3	1309-37-1	0 0	7.25
Magnesium Silicate, inert filler ACGIH TLV: 2 mg/m3, OSHA PEL: 20 Mppcf	14807-96-6	0 0	3.52
Organoclay	68911-87-5		2.04
* Manganese metal as drier compound ACGIH TLV: 5 mg/m3, OSHA PEL: 5 mg/m3 (C)	7439-96-5	0 0	0.01

* indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

LEGEND: (C)=Ceiling limit; (S)=Skinlimit; (STEL)=Short Term Exposure Limit; (Mppcf)=Million Particles Per Cubic Foot; (TWA)=8 HR Time Weighted Average.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 250 deg F SPECIFIC GRAVITY: 1.42
 VAPOR DENSITY: Heavier than air. EVAPORATION RATE: Slower than ether.
 COATING VOC: 2.86 lb/gal MATERIAL VOC: 2.86 lb/gal
 ORGANIC SOLVENT, PERCENT BY WEIGHT: 24.235
 ORGANIC SOLVENT, PERCENT BY VOLUME: 45.714
 COATING DENSITY, LB/GAL: 11.794
 SOLUBILITY IN WATER: Insoluble.
 APPEARANCE AND ODOR: Viscous, opaque liquid with a paint thinner-like odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 54 deg F METHOD USED: TCC
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.2 UPPER: 6

EXTINGUISHING MEDIA: Foam, alcohol foam, CO2, dry chemical, water fog.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus and full protective clothing. Keep onlookers away. Dike runoff to prevent entry into sewers, storm drains, and watercourses. Use caution after fire is extinguished, vapors or liquid may reignite. Notify appropriate state and local agencies.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Pressure may build up in tightly closed containers exposed to fire which may result in rupture. Keep containers cooled

MATERIAL SAFETY DATA SHEET

Page: 2

with water spray. Vapors may travel a considerable distance to a source of ignition or collect in low areas.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable

CONDITIONS TO AVOID: Sources of ignition, poor ventilation, corrosive atmospheres or liquids which may damage containers.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids and bases, oxidizers.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon dioxide, carbon monoxide, and other toxic gases.

HAZARDOUS POLYMERIZATION: Will not occur.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Effects vary among individuals and may include headache, dizziness, nausea, irritation of the nose, throat, and respiratory tract, and incoordination. Severe overexposure may produce anaesthesia or unconsciousness.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Eye contact may cause irritation, redness, and tearing, and blurred vision. Skin contact may cause irritation and redness. Long term skin exposure may dry and defat the skin, causing cracking, and in severe cases, dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Ingestion can cause gastrointestinal irritation, vomiting, nausea, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC): Breathing high concentrations of aerosols or mists of this material may cause nausea and irritation of the nose, throat, and respiratory tract. Acute overexposure to solvent fumes during air drying of this product may cause headache, dizziness, nausea, and loss of coordination. Chronic overexposure to solvent fumes may cause central nervous system damage.

CARCINOGENICITY: NTP: No IARC MONOGRAPHS: No OSHA REGULATED: No

*** NO INFORMATION AVAILABLE FOR THIS SECTION ***

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Overexposure to solvent fumes may aggravate anesthesia, respiratory tract disease or pre-existing lung disorders, nausea, and vomiting.

EMERGENCY AND FIRST AID PROCEDURES: **INHALATION OVEREXPOSURE:** Remove person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention. NOTE: Use supplied-air respirator for rescue in enclosed areas. **EYE CONTACT:** Flush with large amounts of tepid water for at least 15 minutes, get medical attention. **INGESTION:** Do not induce vomiting, if aspirated material can cause chemical pneumonitis or pulmonary edema. Drink 2 glasses of milk or water to dilute and contact physician or poison center. **SKIN:** Wash with soap and water, avoid repeated contact.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Dike to prevent entry into sewers or surface waters. Recover free liquid by shovelling into container using non-sparking tools, or add absorbant.

MATERIAL SAFETY DATA SHEET

Page: 3

such as sand or earth to spill and sweep up. Provide ventilation, wear a respirator. Notify proper authorities if spill contaminates land or waterways.

WASTE DISPOSAL METHOD: Store soaked rags or absorbant material in airtight containers to prevent spontaneous combustion of material. Absorbant materials may emit flammable vapors. Dispose of in chemical landfill or incinerate assuring conformity to all applicable local, state, and federal governing regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not expose to flame, sparks, or other sources of ignition. Use non-sparking alloy tools, and ground or interbond containers when pouring to avoid static discharge. Store inside away from extreme temperature variations. Protect containers from physical damage. Keep containers tightly closed when not in use. Do not inhale vapors or mists. Use with adequate ventilation and wear a respirator. Do not store with food or animal feed.

OTHER PRECAUTIONS: Do not cut, weld, grind, drill, solder, or braze on or near containers whether full or empty. Do not reuse containers without professional reconditioning and testing. Do not remove warning labels from containers.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION: Using this product in poorly ventilated areas may require the use of a respirator. Use Mine Safety Appliance respirator #446849 with organic vapor cartridge and mist filter (or equivalent) if air monitoring demonstrates that the concentration of listed hazardous materials exceeds the recommended TLV's. In enclosed areas where ventilation is not used, wear a Mine Safety Appliance #475217 pressure/demand air-supplied respirator or equivalent.

VENTILATION: Use good general mechanical ventilation and local exhaust adequate to reduce the concentration of vapors or mists of the listed hazardous materials to below the Threshold Limit Value(s) and the Lower Explosion Limit. Ventilation equipment must be explosion proof.

PROTECTIVE GLOVES: Use of gloves is recommended, use chemically resistant type.

EYE PROTECTION: Use is recommended, use splash goggles or full face shields as necessary.

OTHER PROTECTIVE CLOTHING: Use impervious apron or coveralls to prevent contaminating streetclothes which may result in prolonged exposure. The use of head caps or helmets is recommended.

WORK AND HYGIENIC PRACTICES: Eye washes and safety showers in the workplace are recommended. Practice good industrial hygiene when using this product: do not smoke or eat and wash after using. Remove saturated clothing or shoes at once and launder before reuse.

===== SECTION IX - MISCELLANEOUS =====

NOT INFORMATION:

UNNA ID No.: UN 1263
 DOT HAZARD CLASS: 3 (Flammable Liquid)
 DOT HAZARD GROUP: II
 DOT HAZARDOUS MATERIAL PROPER SHIPPING NAME: Flammable Liquid, Paint

DISCLAIMER:

The information and recommendations contained herein were believed to be

MATERIAL SAFETY DATA SHEET

Page: 4

accurate at the time of preparation or obtained from sources believed to be generally reliable. Pruett-Schaffer Chemical Corporation makes no warranty concerning their accuracy and will not be held liable for claims relating to any party's use of or reliance on this information.